

HELVETIA

Arizona Plus

DESCRIPTION

Ultra luxurious Nubuck. Produced from the top 5% of European raw material. Literally the highest end Nubuck on the market.

SPECIFICATIONS

Average Hide Size	55 sqft / 5.11 sqmt
Thickness	1.3 - 1.5 mm

PERFORMANCE CHARACTERISTICS

Light Fastness	(AATCC Method 16, Option E)	3 - 4
Tear Strength	(ASTM D4705)	25 lbs.
Flexing Endurance	(ASTM D2097)	Pass
Abrasion	(ASTM D3884)	N /A
Elongation	(ASTM D2211)	30 - 40% at 50 lbs.
Crocking	(ASTM D5053)	Wet:4 Dry: 4
Breaking Force	(ASTM D2208)	200 lbs.

FLAMMABILITY

Boston Fire Dept. Code (BFD 1x-1) w/Fire Blocker and or Fire Barrier Cloth	Pass
California Technical Bulletin 117	Pass
Cigarette Ignition Resistance (NFPA 260)	Class 1
California Technical Bulletin 133 w/Fire Blocker and/or Fire Barrier Cloth	Pass

CLEANING INSTRUCTIONS

Natural, aniline leathers have little surface protection. If your aniline leather does become soiled, immediately blot excess liquid with a soft, clean cloth. Then clean the entire area (i.e. the entire seat cushion, arm rest, etc.) with a clean, damp cloth and clear luke warm water, starting from the outside of the spill to the center.

Do not use: Any saddle soaps, oils, abrasives, cleaners, soaps, furniture polish, varnish or ammonia water.

Please note: Due to the natural characteristics of this leather, scratches and marks may appear over time. This appearance is the "character" of the natural leather.