

HELVETIA

Metallic

DESCRIPTION

Full grain, drum dyed leather with an understated metallicized finish for a modern look. This product is produced on the finest European raw material.

SPECIFICATIONS

| | |
|-------------------|---------------------|
| Average Hide Size | 55 sqft / 5.11 sqmt |
| Thickness | 1.0 - 1.1 mm |

PERFORMANCE CHARACTERISTICS

| | |
|--|-------------------|
| Light Fastness (AATCC Method 16, Option E) | 4 |
| Tear Strength (ASTM D4705) | 25 lbs. |
| Flexing Endurance (ASTM D2097) | Pass |
| Abrasion (ASTM D3884) | N/A |
| Elongation (ASTM D2211) | 30-50% at 50 lbs. |
| Crocking (ASTM D5053) | Wet 4: Dry:4 |
| Breaking Force (ASTM D2208) | 178 lbs. |

FLAMMABILITY

| | |
|--|---------|
| Boston Fire Dept. Code (BFD 1x1) w/Fire Blocker and or Fire Barrier Cloth | Pass |
| California Technical Bulletin 117 | Pass |
| Cigarette Ignition Resistance (NFPA 260) | Class 1 |
| California Technical Bulletin 133 w/Fire Blocker and/or Fire Barrier Cloth | Pass |

CLEANING INSTRUCTIONS

Natural, aniline leathers have little surface protection. If your aniline leather does become soiled, immediately blot excess liquid with a soft, clean cloth. Then clean the entire area (i.e. the entire seat cushion, arm rest, etc.) with a clean, damp cloth and clear luke warm water, starting from the outside of the spill to the center.

Do not use: Any saddle soaps, oils, abrasives, cleaners, soaps, furniture polish, varnish or ammonia water.

Please note: Due to the natural characteristics of this leather, scratches and marks may appear over time. This appearance is the "character" of the natural leather.